

ELITE SERIES

TETHER ATTACHMENT

Tether Accessory Attachment

GA EMERGENCY MODE

- 1st Press= All LEDs Flashing
- 2nd Press= OFF
- Hold= Scrolling Sequence (Push Again to Turn Off)

BRIGHTNESS SETTINGS

Max, High, Medium, Low or SOS Light Pattern

REAR LED'S

- 1st Press= Constant On
- 2nd Press= Constant Blinking
- 3rd Press= Scrolling Sequence
- 4th Press= OFF
- Hold= Battery Level Indicator



CHARGING PORT

Rechargeable Type-C USB Charging Port (on underside)

DURABLE

Waterproof, Dustproof, Shockproof, IP68 Rated

FRONT LED'S

- 1st Press= Constant On
- 2nd Press= Constant Blinking
- 3rd Press= Scrolling Sequence
- 4th Press= OFF
- Hold On/Off = All Front LEDs

WORK LIGHT

- 1st Press= Single LED On
- 2nd Press= OFF
- Hold= Standard Operating Mode (All Front LED's On, Rear LED's Flashing)

BUILT IN MAGNET

Super Strong Built-in Rare Earth Magnet Mounting System (on underside)

GA guardianangeldevices.com



- +972 58 748 88 60
- +32 488 61 66 17
- +32 2 588 77 93
- +33 1 76 64 13 72



ELITE SERIES PRODUCT SPECS:

- PRODUCT NAME** → Guardian Angel™ Elite™ Series LED Light Bar
- LIGHT SOURCE** → 18 LED'S
- COLORS** → Red, White, Blue, Yellow, Green, Orange, Infrared
- BRIGHTNESS** → Up to 800 lumens (varies by model),
5+ Miles Visibility
- SIZE** → 2.75"W x 1.87" L x 1.0" H
- WEIGHT** → 3.25oz, 92.4g
- BATTERY** → **Type:** Rechargeable Lithium Polymer Battery
Capacity: 1400mAh / 5.18Wh
Charging Time: Approx. 1.5 hrs
Normal Voltage: 3.7V
Certification: UN38.3, IEC62133, CE, RoHS Compliant
Battery Life hr/charge: Varies based on
brightness setting & light mode. 1.5 – 150 hours
Battery Life Cycle: 1500 – 3000 cycles
- CHARGING** → **Connector:** Type C USB
Input: AC 100-240V - 50/60Hz. 0.6A
Output: 5.0V - 2000mA
- CASING** → **Material:** Polycarbonate Lens, Glass Filled
Polycarbonate Exterior Covers and USB Door,
High Temperature Rubber Buttons & Water Seals
IP Rating: IP68 Water/Dust Proof Rating
Flammability Rating: UL 746B, UL94
- MOUNTING** → Neodymium iron boron Grade NB42 magnets
- ENVIRONMENT** → **Operational Temp & Humidity:** -40C°- 110C°
Storage Temp & Humidity: 20-28C°



- +972 58 748 88 60
- +32 488 61 66 17
- +32 2 588 77 93
- +33 1 76 64 13 72