

MICRO SERIES

TETHER ATTACHMENT

Tether Accessory Attachment

GA EMERGENCY MODE

- 1st Press= All LEDs Flashing
- 2nd Press= OFF
- Hold= Scrolling Sequence (Push Again to Turn Off)

BRIGHTNESS SETTINGS

Max, High, Medium, Low or SOS Light Pattern

REAR LED'S

- 1st Press= Constant On
- 2nd Press= Constant Blinking
- 3rd Press= Scrolling Sequence
- 4th Press= OFF
- Hold= Battery Level Indicator

CHARGING PORT

Rechargeable Type-C USB Charging Port (on side)

DURABLE

Waterproof, Dustproof, Shockproof, IP67 Rated



WORK LIGHT

- 1st Press= Single LED On
- 2nd Press= OFF
- Hold= Standard Operating Mode (All Front LED's On, Rear LED's Flashing)

BUILT IN MAGNET

Super Strong Built-in Rare Earth Magnet Mounting System (on underside)

FRONT LED'S

- 1st Press= Constant On
- 2nd Press= Constant Blinking
- 3rd Press= Scrolling Sequence
- 4th Press= OFF
- Hold On/Off = For Top LED



- +972 58 748 88 60
- +32 488 61 66 17
- +32 2 588 77 93
- +33 1 76 64 13 72

MICRO SERIES PRODUCT SPECS:



PRODUCT NAME → Guardian Angel™ Micro™ Series LED Light Bar

LIGHT SOURCE → 11 LEDs

COLORS → Red, White, Yellow, Green, Orange, Infrared

BRIGHTNESS → Up to 500 lumens (varies by model),
3+ Miles Visibility

SIZE → 1.99"W x 1.72"L x 0.68"H

WEIGHT → 2.0 oz, 56.70g

BATTERY → **Type:** Rechargeable Lithium Polymer Battery
Capacity: 500mAh / 1.85Wh
Charging Time: Approx. 3.7 hrs
Normal Voltage: 3.7V
Certification: UN38.3, IEC62133, CE, RoHS Compliant
Battery Life hr/charge: Varies based on
brightness setting & light mode. 2 – 150 hours
Battery Life Cycle: 1500 – 3000 cycles

CHARGING → **Connector:** Type C USB
Input: AC 100-240V - 50/60Hz. 0.6A
Output: 5.0V - 1000mA

CASING → **Material:** Polycarbonate Lens, Glass Filled
Polycarbonate Exterior Covers and USB Door,
High Temperature Rubber Buttons & Water Seals
IP Rating: IP67 Water/Dust Proof Rating
Flammability Rating: UL 746B, UL94

MOUNTING → Neodymium iron boron Grade NB42 magnets

ENVIRONMENT → **Operational Temp & Humidity:** -40C° - 110C°
Storage Temp & Humidity: 20-28C°



+972 58 748 88 60
+32 488 61 66 17
+32 2 588 77 93
+33 1 76 64 13 72