

## MARKET FOCUS: LAW ENFORCEMENT DEVICES

STANDARD DEVICES Each device features red/white/blue or white/blue front LEDs (8), red/blue or all blue rear LEDs (8), a single red LED work light on front (1), enhanced white LED take down lights on front (4), Each side has flashing, strobing or constant-on light patterns which can be independently controlled.



ELT-B/B

BLUE / BLUE FLITE SERIES



ELT-R/B

RED / BLUE ELITE SERIES

INFRARED/HYBRID DEVICES All the features as Standard Law Enforcement Devices, except the LED on top of the device is 850 nanometer Infrared (IR) LED (1), which can be independently controlled.



ELT-B/B-IR

BLUE / BLUE INFRARED HYBRID ELITE SERIES



ELT-R/B-IR

RED / BLUE INFRARED HYBRID ELITE SERIES



ELT-W/R-IR WHITE / RED INFRARED HYBRID ELITE SERIES



ELT-IR

ALL INFRARED ELITE SERIES

\*18 Infrared LED lights. Features the same light pattern settings as the standard devices, but emits NO visible light without the use of night vision equipment.



• LIGHT SOURCE Elite 18 LEDs, Micro 11 LEDs

• COLOR OPTIONS Elite 25 Combinations: Red, White, Blue, Yellow (Amber), Orange, Green, Infrared Micro 11 Combinations: Red, White, Yellow (Amber), Orange, Green, Infrared

• BRIGHTNESS Elite: up to 800 Lumens, 5+ Miles Visibility Micro: up to 500 Lumens, 3+ Miles Visibility

• IR (INFRARED) Hybrid- single 850nm infrared LED on top All-Infrared - 940nm infrared LED Can only be seen using night vision equipment

• BRIGHTEST COLORS White, Green, Yellow

SIZE Elite: 2.75"W x 1.87"L x 1.0"H, Micro 1.99"W x 1.72"L x 0.68"H

WEIGHT Elite: 3.25oz, 92.4g, Micro 2.0oz 56.70g

BATTERY Type: Rechargeable Lithium Polymer

Capacity: Elite: 1400mAh / 5.18Wh, Micro 500mAh / 1.85Wh

Normal Voltage: 3.7V Certification: UN38.3

Run Time/Charge: Elite 1.5 - 150 hrs, Micro 1.0 - 50 hrs

Most common settings Elite 8-12 hrs, Micro 1-3 hrs (continuous)

Battery Life Cycle: Elite 1500 - 3000, Micro 500-3000 cycles w/ regular use

· CHARGING Cord: Type-C to USB

Input: AC 100-240V - 50/60Hz, 0.6A

Output: 5.0V - 2000mA

Charging Time: Elite Approx 1.5 hrs, Micro Approx 50 min.

 CASING Material: Polycarbonate Lens, Glass Filled Polycarbonate Exterior Covers & USB Door, High Temperature Rubber Buttons & Water Seals Hz, 0.6A IP Rating: Elite IP68 Water/Dust Proof Rating, Micro IP67 Water/Dust Proof Rating Flammability Rating: UL 746B, UL94

 MOUNTING Neodymium iron boron Grade NB42 Magnets Optional Hard Mount on select mounts using (2) M3 screws

• ENVIRONMENT Operational Temp & Humidity: -40°C -110°C, -40°F - 230°F Storage Temp & Humidity: 20-28°C, 68-82°F



## **MARKET FOCUS: LAW ENFORCEMENT MOUNTS**

MARKET 10000 : EAW ENTOROEMENT MOUNTO							
	SKU	NAME	APPLICATION	FEATURES	FITS STRAPS UP TO	UNDER STRAP Base width	MORE MM: Nard Mounting Option Sc: Hard Mounting Scrows Included
8	ELT-SCM	Strap & Epaulet Mount	Uniform & Vest Epaulet Straps	Best with thin & tighter straps	1/8" thick & up to 1.5" wide	2.25"	нм, ѕс
9	ELT-JCM	Jaw Clip Mount	Shirt, Jacket, Lapel, Belt, Epaulet, Carrier Vest, Molle	Works with thicker straps, most versatile, easy to handle	1.75" wide	1"	нм, ѕс
0	ELT-UCM	Universal Clip Mount	Radio Strap, Belt, Hat brim, Epaulet, Molle	Works well w/ wider straps, rubber backing for better grip.	1/4" thick and over 2" wide	0.75"	нм, ѕс
	ELT-UCMS	Small Universal Clip Mount	Radio Strap, Belt, Hat brim, Epaulet, Molle	Works well w/ wider straps, Strong clip tension, able to hang on a wall screw.	1/8" thick and over 1.5" wide	0.75"	нм
5	ELT-COSM	Clamp On Strap Magnetic Mount	Radio Strap, Belt, Epaulet, Molle	More robust than ELT- SCM, Good for leaving mount in place, Best mount for Radio Straps.	1/4" thick & 1.5" wide	1.75"	
	ELT-MMB	Base Shoulder Mount	Under clothing & straps	Padded bottom for comfort	Strap guides are 1.75" wide	2.125"	нм, sc
3	ELT-DTS	Device Tether	Device Loss prevention / added security	8.5" Total length, Quick disconnect, Carabiner & Cord Lock			
	ELT-WM	Window/ Dash Mount	Windshield, Dash	2.5" Suction Mount			
	ELT-MCM	Magnetic Cone Mount	Traffic Cones	3-leg design allows the mount to be inserted into any size cone.			нм
	ELT-RBM	Bike/Rail Rubber Strap Mount	Bike, Post/Rail	Able to attach small lock (not included)	0.5"-1.25" diameter post	2.125"	
	ELT-RBSM	Rotatable Bike Strap Mount	Horizontal or Vertical Rail/Pole	Optional Bolting screws included	Mounting Plate 2.75" x 2.375"	1.5"	
7	ELT-BSM	Bike/Rail Strap Mount	Bike, Post/Rail	Rubber backing for grip, 6" x 2" adjustable Velcro Strap	Approx 0.5"- 1.75" diameter post	1.5"	нм, sc
-37	_						



