

MARKET FOCUS: ROADSIDE - CONSTRUCTION - UTILITIES DEVICES

STANDARD DEVICES Each device features all white front LEDs (8), solid or split color rear LEDs (8), a single red LED work light in the front (1), and a white LED light on top (1). Hybrid Models have a single Infrared LED on the top instead of white (1). Each side has flashing, strobing and constant-on light patterns which can be independently controlled.



ELT-W/GY WHITE / GREEN YELLOW

ELITE SERIES



ELT-W/Y WHITE / YELLOW

ELITE SERIES



ELT-W/O WHITE / ORANGE

ELITE SERIES



ELT-W/BY

WHITE / BLUE YELLOW ELITE SERIES

BEACON DEVICES Each device features solid or split color front LEDs (8), solid or split color rear LEDs (8), a single white LED work light in the front (1), and a white LED light on top (1). Each side has flashing, strobing and constant-on light patterns which can be independently controlled.



ELT-GY/GY GREEN YELLOW / GREEN YELLOW

FLITE SERIES



ELT-WY/WY WHITE YELLOW / WHITE YELLOW

ELITE SERIES

 $\begin{tabular}{ll} \textbf{MICRO DEVICES} & Each device features white or solid color front LEDs \\ \end{tabular}$ (4), solid color rear LEDs (5), a single white or red LED work light in the front (1), and a white LED light on top (1). Each side has flashing, strobing and constant-on light patterns which can be independently controlled. Compatible with all Elite Mounting options.



MCR-W/Y

WHITE / YELLOW MICRO SERIES



MCR-W/R

WHITE / RED MICRO SERIES



MCR-Y/Y

YELLOW / YELLOW

MICRO SERIES



• LIGHT SOURCE Elite 18 LEDs, Micro 11 LEDs

• COLOR OPTIONS Elite 25 Combinations: Red, White, Blue, Yellow (Amber), Orange, Green, Infrared Micro 11 Combinations: Red, White, Yellow

(Amber), Orange, Green, Infrared

• BRIGHTNESS Elite: up to 800 Lumens, 5+ Miles Visibility

Micro: up to 500 Lumens, 3+ Miles Visibility

• IR (INFRARED) Hybrid- single 850nm infrared LED on top

All-Infrared - 940nm infrared LED Can only be seen using night vision equipment

• BRIGHTEST COLORS White, Green, Yellow

• SIZE Elite: 2.75"W x 1.87"L x 1.0"H, Micro 1.99"W x 1.72"L x 0.68"H

• WEIGHT Elite: 3.25oz, 92.4g, Micro 2.0oz 56.70g

BATTERY Type: Rechargeable Lithium Polymer

Capacity: Elite: 1400mAh / 5.18Wh, Micro 500mAh / 1.85Wh

Normal Voltage: 3.7V Certification: UN38.3

Run Time/Charge: Elite 1.5 - 150 hrs, Micro 1.0 - 50 hrs

Most common settings Elite 8-12 hrs, Micro 1-3 hrs (continuous)

Battery Life Cycle: Elite 1500 - 3000, Micro 500-3000 cycles w/ regular use

. CHARGING Cord: Type-C to USB

Input: AC 100-240V - 50/60Hz, 0.6A

Output: 5.0V - 2000mA

Charging Time: Elite Approx 1.5 hrs, Micro Approx 50 min.

• CASING Material: Polycarbonate Lens, Glass Filled Polycarbonate

Exterior Covers & USB Door, High Temperature Rubber Buttons & Water Seals Hz, 0.6A IP Rating: Elite IP68 Water/Dust Proof Rating, Micro IP67 Water/Dust Proof Rating

Flammability Rating: UL 746B, UL94

• MOUNTING Neodymium iron boron Grade NB42 Magnets Optional Hard Mount on select mounts using (2) M3 screws

 ENVIRONMENT Operational Temp & Humidity: -40°C -110°C, -40°F - 230°F Storage Temp & Humidity: 20-28°C, 68-82°F





MARKET FOCUS: ROADSIDE - CONSTRUCTION - UTILITIES MOUNTS

	SKU	NAME	APPLICATION	FEATURES	FITS STRAPS UP TO	UNDER STRAP BASE WIDTH	MORE HM: Hard Mounting Option SC: Hard Mounting Scrows Included
	ELT-HHM	Hard Hat Mount	Hard Hat / Helmet	Magnet Disk applies to inside of the helmet w/ adhesive			
	ELT-MCM	Magnetic Cone Mount	Traffic Cones	3-leg design allows the mount to be inserted into any size cone			нм
0	ELT-UCM	Universal Clip Mount	Radio Strap, Belt, Hat brim, Epaulet, Molle	Works well w/ wider straps, rubber backing for better grip	1/4" thick and over 2" wide	0.75"	нм, ѕс
	ELT-UCMS	Small Universal Clip Mount	Radio Strap, Belt, Hat brim, Epaulet, Molle	Works well w/ wider straps, Strong clip tension, able to hang on a wall screw	1/8" thick and over 1.5" wide	0.75"	нм
	ELT-WM	Window Mount	Windshield, Dash	2.5" Suction Mount			
	ELT-HHMS	Helmet Strap w/ 2 Magnetic Mounts	Fire Helmets, Thicker Hard Hats, Safety Helmets	28" x 7/8" stretch adjustable strap		0.8"	нм, ѕс
	ELT-MMB	Base Shoulder Mount	Under clothing & straps	Padded bottom for comfort	Strap guides are 1.75" wide	2.125"	
09	ELT-MSML ELT-MSMS	Arm Strap w/ Magnetic Mount	Arm or Over Clothes	19.5" x 2" OR 15" x 2" Adjustable Velcro strap		2"	
	ELT-DTS	Device Tether	Device Loss prevention / added security	8.5" Total length, Quick disconnect, Carabiner & Cord Lock	L		1



